

TURNTABLES: ELECTRIC/PNEUMATIC

Standard Features:

- Table Diameters: 72", 75", 78", 82", 84", 86" and 92"
- Welded, Structural Steel Frame Construction
- 230-460/3/60 Primary Voltage
- 4,000 Lbs. Maximum Capacity with Centered Load
- High Side CDLR Drive Mounting
- 30, 45 and 60 FPM Fixed Conveyor Speeds
- 90°, 180°, 270° or Continuous Rotation
- Scalloped Type Roller Chain Guard #10 Ga. and #16 Ga. Drive Chain Guard
- Adjustable Heavy Duty Channel Supports
- Painted Alba Blue with Safety Yellow Guards
- Shipped Fully Assembled for Easy Installation
- Fully Tested Prior to Shipment



Optional Items:


- VFD (Variable Frequency Drive) Rated Motors
- Transition Rollers
- Color Match Paint to Specifications



Turntables: Electric/ Pneumatic

Alba Product Specifications

Centers	Chain	Effective Widths	Table Diameter
2.75" DBS	RC-40 Chain	44"	72"
		48"	75"
		52"	78"
		54"	78"
		60"	86"
3.25"	RC-40 Chain	44"	72"
		48"	78"
		52"	84"
		54"	84"
		60"	86"
3.75"	RC-40 Chain	44"	72"
		48"	78"
		52"	84"
		54"	84"
		60"	86"
4"	RC-40 Chain	44"	72"
		48"	78"
		52"	78"
		54"	86"
		60"	86"
6"	RC-40 Chain	44"	72"
		48"	78"
		52"	84"
		54"	84"
		60"	86"
3.75"	RC-60 Chain	44"	78"
		48"	84"
		52"	84"
		54"	86"
		60"	92"
4.50"	RC-60 Chain	44"	72"
		48"	78"
		52"	82"
		54"	86"
		60"	86"
6"	RC-60 Chain	44"	72"
		48"	78"
		52"	84"
		54"	84"
		60"	86"



detail shown of product above

