

Pflow Series M Mechanical Vertical Lift DIMENSIONS & DATA

Straddle Carriage Cantilever Carriage FL EFF. CARRIAGE WIDTH MIN. OPENING LENGTH A + 28" (FOR SHAFT APPLICATION) 3" MIN. RECOMMENDED CLEARANCE OVERALL LIFT HEIGHT E + F + 30" MIN *//////*} *{/////* **-**(////) E EFFECTIVE CARRIAGE HEIGHT 7'-0" STANDARD D CARRIAGE THICKNESS (4 1/4" STD.) OVERALL LIFT LENGTH A+21 **A** Eff. Carriage Length: Load Size: A Eff. Carriage Length: Load Size: Load Weight: **B** Overall Carriage (L): **B** Overall Carriage (L): Load Weight: Loads Per Hour: **C** Eff. Carriage Width: Loads Per Hour: **C** Eff. Carriage Width: **D** Carriage Thickness: Location: Interior **D** Carriage Thickness: Location: 🖵 Interior **E** Load Height: ☐ Exterior □ Exterior **E** Load Height: **F** Vertical Rise: **F** Vertical Rise: **H** Upper Level Opening (Length): **H** Upper Level Opening (Length): I Upper Level Opening (Width): I Upper Level Opening (Width):

Note: The dimensions shown are illustrative. Request a job-specific drawing before making any building modifications.

