


WHEEL

Model "FX 200" Heavy-Duty

A proven performer for trailer loading and unloading. Ideally suited for packaging, shipping and flexible assembly lines. Order optional leg connect brackets to lock units together.

- **Structural Steel Support:** Channel steel spans the entire conveyor width for unequalled strength.
- **1 ¼" Side Plates:** Aluminum alloy with ribbed construction for added durability. Assembled with shoulder bolts.



| Model Number | Width | Compacted to Expanded | Conveyor Height | Leg Sets Per Unit | Wheels Per Axle | Unit Weight |
|------------------|--------|-----------------------|-----------------|-------------------|-----------------|-------------|
| FX200-18-12-ST-5 | 18 in. | 3 ft. to 12 ft. | 28 ½" to 41 ½" | 4 | 7 | 215 lbs. |
| FX200-18-24-ST-5 | 18 in. | 6 ft. to 24 ft. | 28 ½" to 41 ½" | 7 | 7 | 429 lbs. |
| FX200-24-12-ST-5 | 24 in. | 3 ft. to 12 ft. | 28 ½" to 41 ½" | 4 | 9 | 252 lbs. |
| FX200-24-24-ST-5 | 24 in. | 6 ft. to 24 ft. | 28 ½" to 41 ½" | 7 | 9 | 504 lbs. |

**24 HOUR SHIPMENT SUBJECT TO AVAILABLE STOCK
24 HOUR SHIPMENT NOT GUARANTEED.**

• STANDARD SPECIFICATIONS

WIDTHS—18 in. and 24 in.

FRAME—Flexible and extendible.

LENGTHS—12 ft. and 24 ft.

EXPANSION RATIO—4:1

FLOOR SUPPORTS—Adjustable type 28 ½" to 41 ½".

WHEELS—1.9 in. dia. with ¼ in. bore.

PACKAGE STOP—Folds down when not in use.

CASTERS—Swivel casters with locking brake.

CAPACITY—200 lbs. capacity per linear foot.

• OPTIONAL EQUIPMENT

LEG CONNECT BRACKETS—Connecting two or more conveyors.

